

This industrial-duty, rechargeable lantern features a bright 615 lumens of light in a smooth flood pattern.



6 LEDs wide pattern parabolic reflectors produce a smooth flood pattern; optimized electronics provide regulated intensity

Two levels of lighting:

- High: 615 lumens; 126m beam distance; runs 8 hours
- Low: 330 lumens; 93m beam distance; runs 18 hours

Standard System – International safety orange or high visibility yellow: includes shoulder strap; includes AC and DC chargers and mounting rack; ideal for field maintenance, inspection of construction sites and remote equipment.

Vehicle Mount System – International safety orange or high visibility yellow: comes with vehicle-mountable hard-wire rack and shoulder strap.

Power Failure System – International safety orange: includes AC and DC chargers and “smart” power failure circuitry automatically illuminates when the E-Flood LiteBox when the power goes off.

IPX4-rated for water-resistance

11.5 in. (29.21 cm); 7 lbs. (3.58kg)

Rack meets requirements of NFPA 1901-14.1.11.2 (2016) mounted in any position

Limited Lifetime Warranty

Visit streamlight.com for full warranty information

	<u>Orange</u>	<u>Yellow</u>
E-Flood LiteBox Standard System - 120V/100V AC/12V DC	45801	45821
E-Flood LiteBox Standard System - 230V AC/12V DC	45802	45822
E-Flood LiteBox Standard System - 240V AC/12V DC	45803	45823
E-Flood LiteBox Vehicle Mount System	45805	45825
E-Flood LiteBox Power Failure System - 120V AC/12V DC	45807	---
E-Flood LiteBox Power Failure System - 230V AC/12V DC	45808	---
E-Flood LiteBox - without charger	45806	45826