

**Zone 0 gas and Zone 20 dust-rated.**  
**Increased output with added features, the ATEX rated Survivor X right-angle torch is available as a fully rechargeable system or an economical alkaline model that provides a 25% cost savings on batteries.**



Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation



New charger design:

- Survivor X securely locks into the charger - fits snugly in place
- Quick release latch for one-handed grab-and-go
- Easy to remove with gloved hands



Rubber dome push-button switch easy to use with gloves  
 Features battery life indicator

Battery life indicator in switch:  
 – Green indicates full charge  
 – Turns red when battery is nearing low voltage  
 – Flashes red continuously when 15 minutes left of battery life

Unbreakable polycarbonate lens with silicone anti-scratch coating  
 Specialized optic combines low profile with strong performance and a wide beam

Rugged nylon polymer body is virtually indestructible



High, low and emergency flash modes:

- High for a super-bright, smoke piercing beam: 250 lumens; 447m beam distance; runs 3.75 hours (Li-ion); runs 5 hours (alkaline)
- Low for longer run time: 60 lumens; 237m beam distance; runs 15 hours (Li-ion); runs 15 hours (alkaline)
- Flash for signaling: runs 8 hours

Optimized electronics provide regulated intensity

IP67-rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested

Uses rechargeable lithium-ion battery (charges in 5 hours) or three alkaline batteries

ATEX/IECEx/UKEx: II 1G Ex ia IIC T3/T4 Ga; II 2D Ex ib IIIB T270°C Db

CE/UKCA: Meets applicable European Community Directives

Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)

Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position

17.9 cm; Li-ion: 346g; Alkaline: 363g

Limited Lifetime Warranty

Visit [streamlight.com](http://streamlight.com) for full warranty information

#90970 - Survivor X ATEX - Alkaline - Orange

#90972 - Survivor X ATEX - 100V AC/12V DC - Orange

#90973 - Survivor X ATEX - 230V AC/12V DC - Orange

#90974 - Survivor X ATEX - 240V AC/12V DC - Orange