



STREAMLIGHT®

SL-SIDESADDLE®



IPX7

	SPOT		FLOOD		COMBO	
	HIGH	LOW	HIGH	LOW	HIGH	LOW
LUMENS	250	60	235	60	300	110
CANDELA	2,500	715	215	55	1,900	660
DISTANCE	100m	53m	29m	15m	87m	51m
RUN TIME	6.75 hrs	12 hrs	6.5 hrs	16 hrs	5 hrs	6.75 hrs

SL-SIDESADDLE® USB



IPX7

	SPOT		FLOOD		COMBO	
	HIGH	LOW	HIGH	LOW	HIGH	LOW
LUMENS	350	100	325	85	400	160
CANDELA	4,250	1,200	300	75	2,400	960
DISTANCE	130m	69m	35m	17m	98m	62m
RUN TIME	6.25 hrs	12 hrs	7 hrs	12 hrs	5 hrs	7 hrs



ALKALINE MODEL



USB MODEL



Description	Yellow	Black
SL-SideSaddle - Includes hard hat mount kit (baseplate, slot strap and universal Y-strap) and (3) AAA alkaline batteries	61630	61620
SL-SideSaddle Hat Light - Includes (3) AAA alkaline batteries and hat mount	61636	61626

Size and Weight	Battery
3" (7.6 cm); 3.4 oz (95g)	(3) AAA alkaline batteries

Description	Yellow	Black
SL-SideSaddle USB - Includes hard hat mount kit (baseplate, slot strap and universal Y-strap), USB-C cord and (1) lithium polymer battery	61631	61621
SL-SideSaddle USB Hat Light - Includes (1) lithium polymer battery, USB-C cord and hat mount	61637	61627

Size and Weight	Battery
3" (7.6 cm); 3.1 oz (88g)	(1) Lithium polymer battery

**A UNIVERSAL FIT
SL-SIDESADDLE®,
ADAPTABLE. RELIABLE. HAT & HELMET COMPATIBLE.**

Safety Helmets



Full Brim Hard Hats



Hats and Bump Caps



Traditional Hard Hats



USB HAZ-LO® HEADLAMP



	SPOT	FLOOD	COMBO
LUMENS	190	120	250
CANDELA	2,000	90	--
DISTANCE	89m	19m	--
RUN TIME	7.5 hrs	13 hrs	7 hrs



Class I, II, Div. 1,
Grps. A, B, C, D, E, F, G
Class III, Cl. 1, Zn 0, IIC
T-Code: T4

- Rechargeable, C1DI headlamp
- Charge indicator LEDs: Red = Charging; Green = Charged; recharges in 4.5 hours
- Multi-function push-button switch



Description	Streamlight
USB HAZ-LO Headlamp - 120V AC - Includes elastic headstrap, rubber hard hat strap and 3M® Dual Lock® - Yellow - Black	61460

Size and Weight	Battery
1.72" (4.36 cm); 4.1 oz (116.2g)	Lithium-ion

ENDURO® PRO HAZ-LO®



	SPOT	FLOOD	COMBO
LUMENS	160	160	235
CANDELA	1,350	100	--
DISTANCE	73m	20m	--
RUN TIME	5 hrs	5 hrs	4.75 hrs



Permissible Portable Headlamp Assembly
App. No. 20-A070001-0
Tested for use in methane-air mixtures only



Class I, II, Div. 1,
Grps. A, B, C, D, E, F, G;
Class III, Class 1, Zn 0,
Grps. IIC, Exia
T-Code: T4

- Intrinsically safe headlamp with spot, flood and combo modes
- Multi-function switch remembers the last mode used
- 45° tilting head



Description	Streamlight
Enduro Pro HAZ-LO - Includes (3) AAA alkaline batteries, elastic headstrap, rubber hard hat strap and 3M® Dual Lock® - Yellow	61424

Size and Weight	Battery
2.19" (5.68 cm); 3.5 oz (99.2g)	(3) AAA alkaline

VANTAGE® II

- Low-profile helmet light designed to easily attach to slotted industrial hard hat mounts
- Safety features includes a blue taillight LED so you can be scene from behind
- Large push-button switch for easy on/off

	HIGH	LOW
LUMENS	350	135
CANDELA	3,500	1,700
DISTANCE	118m	80m
RUN TIME	2.25 hrs	5 hrs



Description	Item #
Vantage II - Industrial - Includes (1) CR123A lithium battery - Black	69333
Bracket Kit	69336

Size and Weight	Battery
2.37" (6.02 cm); 2.97 oz (84.2g)	(1) CR123A lithium



IPX7

NFPA

Flashlight meets 500°F requirements of
NFPA 1970-14.2 (2025)

